



(239) 938-1000 | StormSmart.com

CLEANING INSTRUCTIONS

STORM CATCHER® SCREENS

Storm Catcher Screens should be washed with a mild detergent and the tracks lubricated with a food-grade silicone lubricant (we recommend Sprayon Lubricant spray) at least two (2) times per year. Begin with sweeping the screens free of any obvious debris. Using a sponge, clean the screen with a solution of one cup mild detergent, like Dawn, and three (3) gallons of warm water. Follow by rinsing with clean water and wipe dry with soft cloth.

STEEL PANELS

Stainless steel will hold its appearance and remain free of corrosion (staining) if it is washed regularly. For best results, wash with soap or mild detergent and warm water. Follow by rinsing with clean water and wipe dry with soft cloth. Do not use hydrochloric acid, or similar, on the product. Never use steel wool.

ACCORDIAN SHUTTERS

Accordion shutters have some stainless-steel parts. Stainless steel is used because of its high resistance to corrosion. Although the metal itself is corrosion resistant, localized corrosion can occur from atmospheric conditions depositing organic particles on the metal that will contaminate the surface. Localized corrosion does not affect the structural integrity or the longevity of the parts. Localized corrosion is controlled with regular cleaning. Life expectancy of your shutters increases with proper care and maintenance. You will want to

use your best judgment and adjust these instructions depending on your climate and particular environment. Clean products free of sand, salt and debris and properly lubricate tracks with a silicone-based lubricant (we recommend L.C. Wax Alumaslick Aluminum Lubricant spray) for best results. Operate the shutters as often as possible to be assured they are functional when needed.